

# Max-Blade Type Automotive Fuse

Gold Plating




Part No. **1501** series



- Slow Blow, Low Voltage For Up To 32V DC
- Material: \* Body: Plastic  
\* Metal: Zinc Alloy with Gold Plating
- Standard: According To SAE J1888
- High Performance For Car Audio System
- Circuit Protection To Replace Fusible Wire Or Fusible Link
- Fuses Are Color-Coded For Easy Amperage Identification



RoHS



Scale: mm

## Specifications

### Opening Time / Pre-arcing Time:

| In      | 1.0 In     | 1.35 In |        | 2.0 In |      | 3.5 In |      | 6.0 In |      |
|---------|------------|---------|--------|--------|------|--------|------|--------|------|
| 20-120A | >100 Hours | Min.    | Max.   | Min.   | Max. | Min.   | Max. | Min.   | Max. |
|         |            | 60 s    | 3600 s | 2 s    | 60 s | 0.2 s  | 7 s  | 0.04 s | 1 s  |

Interruption Ratings: 1000 Amperes @32VDC

### Ordering Information:

| Part Number | Ampere (A) | Voltage (VDC) | Body Color |
|-------------|------------|---------------|------------|
| 15012200200 | 20 A       | 32 V          | Yellow     |
| 15012300200 | 30 A       | 32 V          | Green      |
| 15012350200 | 35 A       | 32 V          | Brown      |
| 15012400200 | 40 A       | 32 V          | Orange     |
| 15012500200 | 50 A       | 32 V          | Red        |
| 15012600200 | 60 A       | 32 V          | Blue       |
| 15012700200 | 70 A       | 32 V          | Tan        |
| 15012800200 | 80 A       | 32 V          | ⊖ Natural  |
| 15013100200 | 100 A      | 32 V          | Violet     |
| 15013120200 | 120 A      | 32 V          | Purple     |