

Max-Blade Type Automotive Fuse






RoHS

Part No. **1502** series



- Slow Blow, Low Voltage For Up To 32V DC
- Material: * Body: Plastic
* Metal: Zinc Alloy
- Standard: According To SAE J1888
- Circuit Protection To Replace Fusible Wire Or Fusible Link
- Fuses Are Color-Coded For Easy Amperage Identification



Scale: mm

Specifications

Opening Time / Pre-arcing Time:

In	1.0 In	1.35 In		2.0 In		3.5 In		6.0 In	
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
20-120A	>100 Hours	60 s	3600 s	2 s	60 s	0.2 s	7 s	0.04 s	1 s

Interruption Ratings: 1000 Amperes @32VDC

Ordering Information:

Part Number	Ampere (A)	Voltage (VDC)	Body Color
15022200200	20 A	32 V	● Yellow
15022300200	30 A	32 V	● Green
15022350200	35 A	32 V	● Brown
15022400200	40 A	32 V	● Orange
15022500200	50 A	32 V	● Red
15022600200	60 A	32 V	● Blue
15022700200	70 A	32 V	● Tan
15022800200	80 A	32 V	⊖ Natural
15023100200	100 A	32 V	● Violet
15023120200	120 A	32 V	● Purple