



**SPECIFICATIONS :**

- Suitable Rated Current : 30A Max.
- Dielectric Strength for 60 seconds : AC1500V Min.
- Insertion & Extraction Force : 1Kg. Min.
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Voltage Drop : 20mV Max.
- Temperature Rise : 50°C Max.
- Molded Parts : Nylon with Glass Fiber
- Terminals : Brass
- Style : Double Fuse Quick Insert Type

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material		Drawn	<b>GLORYTECH TECHNOLOGY CO., LTD.</b>			
Finish		Check	Title:		A	B
		Engr	<b>Mounted Fuse Block</b>			
		Appd			<b>GTQD-BLK-1829-1911</b>	
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)			Scale:	1:1	Dwg Size	Sht 1 of 1
Model File Name : Mounted Fuse Block for Blade Type Fuses						
Drawing File Name : GTQD-BLK-1829-1911						
Part Number : 1829 1911 400					Date:	2004/9/24