



SPECIFICATIONS :

Suitable Rated Current : 300A Max.

Dielectric Strength for 60 seconds : AC500V Min.

Contact Resistance at 1A DC : 5mΩ Max.

Insulation Resistance at 500V DC : 100MΩ Min.

Molded Parts : Flame Retarding, Phenolic Laminate

Contacts : Steel, anti-corrosion

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material		Drawn	GLORYTECH TECHNOLOGY CO., LTD.			
Finish		Check	Title:		A	B
		Engr	Fuse Block			
		Appd			GTQD-BLK-1911-0103	
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)			Scale:	1 : 1	Dwg Size	Sht 1 of 1
Model File Name : Fuse Block for (1307,1308,1555,1539) Fuse Link						
Drawing File Name : GTQD-BLK-1911-0103						
Part Number : 1911 0103 000					Date:	2005/9/15