



SPECIFICATIONS :

- Suitable Rated Current : 500A Max.
- Dielectric Strength for 60 seconds : AC500V Min.
- Ambient Temperature : -40°C ~ 125°C
- Climatic Catagory : -40°C ~ 85°C
- Operating Temperature : -40°C ~ 125°C
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Molded Parts : Flame Retarding, Phenolic Laminate
- Contacts : Steel, anti-corrosion

Tolerances : Unless Otherwise Specified	
Dimension	Critical To Function
< 1	+/-0.02
1 ~ 8	+/-0.1
8 ~ 24.995	+/-0.15
25 ~ 99.99	+/-0.2
Angles	+/- 1°
Rev	EN
93092401	Modify the tolerance
	Dwg Kao
	Ckdi Chyi
	Appd Ku
	Date 2004/9/24

Material		Material		Material	
Drawn	Check	Engr	Appd	Drawn	Check
Finish		Title:		Finish	
Unless Otherwise Specified		Heavy Duty Fuse Block		Dimensions are mm (inch)	
Tolerances:		Scale:		Title:	
.x = 1.0 (.04)		1 : 1		Heavy Duty Fuse Block	
.xx = 0.5 (.02)		Dwg Size		A4	
.xxx = 0.25 (.010)		Sht		GTQD-BLK-1911-0104	
Model File Name : Heavy Duty Fuse Block (MEGA)		of		B	
Drawing File Name : GTQD-BLK-1911-0104		1		1	
Part Number : 1911 0104 000		Rev		Date:	
				2013/9/14	