



SPECIFICATIONS :

- Suitable Rated Current : 800A Max.
- Dielectric Strength for 60 seconds : AC500V Min.
- Ambient Temperature : -40°C ~ 125°C
- Climatic Catagory : -40°C ~ 85°C
- Operating Temperature : -40°C ~ 125°C
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Molded Parts : Flame Retarding, Phenolic Laminate
- Contacts : Brass, anti-corrosion

Tolerances : Unless Otherwise Specified	
Dimension	Critical To Function
< 1	+/- 0.02
1 ~ 8	+/- 0.1
8 ~ 24.995	+/- 0.15
25 ~ 99.99	+/- 0.2
Angles	+/- 1°
Rev	EN
93092401	Modify the tolerance
	Dwg Kao
	Ckd Chyi
	Appd Ku
	Date 2004/9/24

Material	Drawn	GLORYTECH TECHNOLOGY CO., LTD. Title: Heavy Duty Fuse Block		
	Check			
Finish	Engr	A4	GTQD-BLK-1911-0107	
	Appd			B
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale:	1 : 1	
Model File Name : Heavy Duty Fuse Block Drawing File Name : GTQD-BLK-1911-0107 Part Number : 1911 0107 000		Dwg Size	Sht 1 of 1	Rev
		Date:	2016/8/23	