



SPECIFICATIONS :

- Suitable Rated Current : 500A Max.
- Dielectric Strength for 60 seconds : AC500V Min.
- Climatic Category : -40°C ~ 85°C
- Operating Temperature : -40°C ~ 125°C
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Molded Parts : Flame Retarding, Phenolic Laminate
- Contacts : Steel, anti-corrosion
- Stud : M8 x 1.25
- Torque : 8.5Nm(75 IN-LBS)

Tolerances : Unless Otherwise Specified

Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Material	Drawn	GLORYTECH TECHNOLOGY CO., LTD.			
	Check				
Finish	Engr	Title: Heavy Duty Fuse Block	A4	GTQD-BLK-1911-0108	B
	Appd				
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale: 1 : 1	Dwg Size	Sht 1 of 1	Rev
Model File Name : Heavy Duty Fuse Block for (1506,1547,ANL) Fuse Link					
Drawing File Name : GTQD-BLK-1911-0108					
Part Number : 1911 0108 000			Date: 2021/8/5		

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24