



**SPECIFICATIONS :**

- Suitable Rated Current : 500A Max.
- Dielectric Strength for 60 seconds : AC500V Min.
- Climatic Category : -40°C ~ 85°C
- Operating Temperature : -40°C ~ 125°C
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Molded Parts : Flame Retarding, Phenolic Laminate
- Contacts : Steel, anti-corrosion
- Stud : M8 x 1.25
- Torque : 8.5Nm(75 IN-LBS)

Tolerances : Unless Otherwise Specified						
Dimension	Critical To Function		General			
< 1	+/- 0.02		+/- 0.03			
1 ~ 8	+/- 0.1		+/- 0.2			
8 ~ 24.995	+/- 0.15		+/- 0.25			
25 ~ 99.99	+/- 0.2		+/- 0.3			
Angles	+/- 1°		+/- 5°			
Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	<b>GLORYTECH TECHNOLOGY CO., LTD.</b>			
	Check				
Finish	Engr	Title: <b>Heavy Duty Fuse Block</b>	A4	GTQD-BLK-1911-0109	B
	Appd				
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale: 1 : 1	Dwg Size	Sht 1 of 1	Rev
Model File Name : Heavy Duty Fuse Block (MEGA)					
Drawing File Name : GTQD-BLK-1911-0109					
Part Number : 1911 0109 000			Date:	2021/8/5	