



**MOUNTING HOLES**

**Fuse Size**

**SPECIFICATIONS :**

- Current Rating : 40 ~ 275A Max.
- Fuse Specifications : For use with MEGA fuse
- Voltage : 32 VDC
- Temperature Rating : -40°C ~ 125°C
- Termination : M8 threaded studs and hex nuts for fuse mounting
- Torque Rating : 20 in-lb(2.25Nm) max.
- Mount Torque Rating : 12-18Nm max.
- Material**
- Cover : Nylon-66(Black)
- Housing : PBT(Black)
- Screw : Ni-Plated Steel Studs
- Notes : Fuse not included
- M8 screws with washers (recommended)

Tolerances : Unless Otherwise Specified	
Dimension	Critical To Function
< 1	+/-0.02
1 ~ 8	+/-0.1
8 ~ 24.995	+/-0.15
25 ~ 99.99	+/-0.2
Angles	+/-1°
Rev	EN
93092401	Modify the tolerance
	Kao
	Chyi
	Ku
	2004/9/24
Description	Dwg
	CKd
	Appd
	Date

<b>Material</b>		<b>Material</b>	
Drawn	Check	Drawn	Check
Engr	Appd	Engr	Appd
Finish		Title:	
Unless Otherwise Specified		<b>Bolt-In Fuse Block</b>	
Dimensions are mm (inch)		A4	
Tolerances:		GTQD-BLK-1917-0109	
.x = 1.0 (.04)		Dwg	
.xx = 0.5 (.02)		Size	
.xxx = 0.25 (.010)		Sht	
Scale:		1	
Model File Name : Bolt-In Fuse Block for Fuse Strip		of	
Drawing File Name : GTQD-BLK-1917-0109		1	
Part Number : 1917 0109 000		Rev	
Date:		2018/1/16	

**GLORYTECH TECHNOLOGY CO., LTD.**