



M6x15mm Hex Screw (x2)

Solid Brass

**SPECIFICATIONS :**

Suitable Rated Current : 300A Max.

Dielectric Strength for 60 seconds : AC500V Min.

Contact Resistance at 1A DC : 5mΩ Max.

Insulation Resistance at 500V DC : 100MΩ Min.

Molded Parts : Nylon with Glass Fiber

Terminals : Brass

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material		Drawn	<b>GLORYTECH TECHNOLOGY CO., LTD.</b>			
Finish		Check	<b>Title:</b>			
		Engr	<b>Mounted Fuse Block</b>		<b>A4</b>	<b>GTQD-BLK-1919-0103</b>
		Appd				<b>B</b>
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)			Scale: 1:1		Dwg Size	Sht 1 of 1
Model File Name : Mounted Fuse Block for MEGA ( 1537,1549 ) Fuse			Rev			
Drawing File Name : GTQD-BLK-1919-0103						
Part Number : 1919 0103 000			Date:		2007/2/27	