



SPECIFICATIONS :

- Suitable Rated Current : 6.3A 250V AC Max.
- Dielectric Strength for 60 seconds : AC2000V Min.
- Insertion & Extraction Force : 1Kg. Min.
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Voltage Drop : 20mV Max.
- Temperature Rise : 50°C Max.
- Molded Parts : Nylon 94V0
- Terminals : Brass
- Approval : UL Recognized E256971

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24
C	94120604	圖面修改	Chris	Bruce	Chyi	2005/12/6

Material		GLORYTECH TECHNOLOGY CO., LTD.			
Drawn	Check	Title:		A4	C
Finish	Engr	P.C.B. Fuse Block		GTQD-BLK-1937-0504	Rev
	Appd	Scale:	2:1	Dwg Size	Sht 1 of 1
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)					
Model File Name : P.C.B. Fuse Block for 5x20mm Fuses					
Drawing File Name : GTQD-BLK-1937-0504					
Part Number : 1937 0504 424				Date:	2005/12/6