



SPECIFICATIONS :

- Suitable Rated Current : 15A Max.
- Dielectric Strength for 60 seconds : AC1500V Min.
- Insertion & Extraction Force : 1Kg. Min.
- Ambient Temperature : -40°C ~ 85°C
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Voltage Drop : 20mV Max.
- Temperature Rise : 50°C Max.
- Molded Parts : Flame Retarding 94V0 Thermoplastic
- Terminals : Brass

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	GLORYTECH TECHNOLOGY CO., LTD.				
	Check					
Finish	Engr	Title:		A	GTQD-BLK-1939-1102	B
	Appd	Fuse Block				
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale: 1:1		Dwg Size	Sht 1 of 1	Rev
Model File Name : Fuse Block for Mini Blade Type Fuse						
Drawing File Name : GTQD-BLK-1939-1102						
Part Number : 1939 1102 400				Date:	2004/9/24	