



Mounting Detail

SPECIFICATIONS :
 Suitable Rated Current : 15A Max.
 Dielectric Strength for 60 seconds : AC1500V Min.
 Insertion & Extraction Force : 1Kg. Min.
 Contact Resistance at 1A DC : 5mΩ Max.
 Insulation Resistance at 500V DC : 100MΩ Min.
 Voltage Drop : 20mV Max.
 Temperature Rise : 50°C Max.
 Molded Parts : Flame Retarding 94V0 Thermoplastic
 Terminals : Brass with Tin Plated
 Operating Temperature Range: -40 °C ~ +125 °C

Tolerances : Unless Otherwise Specified				
Dimension	Critical To Function	General		
< 1	+/-0.02	+/-0.03		
1 ~ 8	+/-0.1	+/-0.2		
8 ~ 24.995	+/-0.15	+/-0.25		
25 ~ 99.99	+/-0.2	+/-0.3		
Angles	+/-1°	+/-5°		
Rev	EN	Description	Dwg	Ckd
B	93092401	Modify the tolerance	Kao	Chyi
				Ku
				2004/9/24

Material	Drawn	GLORYTECH TECHNOLOGY CO., LTD. Title: Fuse Block			
	Check				
Finish	Engr	Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)	A4	GTQD-BLK-1939-1105	B
	Appd				
Scale:		2:1	Dwg Size	Sht	1 of 1
Model File Name :		3 Clip Fuse Block for Mini Blade Type Fuse			
Drawing File Name :		GTQD-BLK-1939-1105			
Part Number :		1939 1105 400			
Date:		2019/11/29			