



MOUNTING DETAIL

**SPECIFICATIONS :**

Suitable Rated Current : 30A Max.  
 Dielectric Strength for 60 seconds : AC1500V Min.  
 Insertion & Extraction Force : 1Kg. Min.  
 Contact Resistance at 1A DC : 5mΩ Max.  
 Insulation Resistance at 500V DC : 100MΩ Min.  
 Voltage Drop : 20mV Max.  
 Temperature Rise : 50°C Max.  
 Molded Parts : Flame Retarding 94V0 Thermoplastic  
 Terminals : Brass , 0.35t

Part No.	Terminal
1939 1907 424	Bright Tin Plated
1939 1907 724	Matte Tin Plated

Tolerances : Unless Otherwise Specified						
Dimension	Critical To Function	General				
< 1	+/-0.02	+/-0.03				
1 ~ 8	+/-0.1	+/-0.2				
8 ~ 24.995	+/-0.15	+/-0.25				
25 ~ 99.99	+/-0.2	+/-0.3				
Angles	+/-1°	+/-5°				
Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	Title:	Dwg	Sht	1	of	1	Rev
	Check							
Finish	Appd	Unless Otherwise Specified Dimensions are mm (inch)	Scale:	1:1				
Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Model File Name : Fuse Block for Blade Fuse						
Drawing File Name : GTQD-BLK-1939-1907		Date: 2004/9/24						
Part Number : 1939 1907 *24		Date: 2004/9/24						

**GLORYTECH TECHNOLOGY CO., LTD.**