



SPECIFICATIONS :

Suitable Rated Current : 80A Max.
 Dielectric Strength for 60 seconds : AC1500V Min.
 Insertion & Extraction Force : 1Kg. Min.
 Contact Resistance at 1A DC : 5mΩ Max.
 Insulation Resistance at 500V DC : 100MΩ Min.
 Voltage Drop : 20mV Max.
 Temperature Rise : 50°C Max.
 Molded Parts : Glass filled Nylon UL94V-0
 Terminals : Phosphor Bronze
 Ambient Temperature : -50 °C ~ +145 °C

Part No.	Terminal
1939 2902 400	Bright Tin Plated
1939 2902 700	Matte Tin Plated

Tolerances : Unless Otherwise Specified	
Dimension	Critical To Function
< 1	+/-0.02
1 ~ 8	+/-0.1
8 ~ 24.995	+/-0.15
25 ~ 99.99	+/-0.2
Angles	+/- 1°

Rev	EN	Description	Dwgt	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material		Finish		Title:	
Drawn	Check	Engr	Appd	Fuse Block	
				A4 GTQD-BLK-1939-2902	
Unless Otherwise Specified Dimensions are mm (inch)				Scale: 2:1	
Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)				Dwg Size	Sht 1 of 1
Model File Name : Fuse Block for Max Blade Type Fuse				Date: 2013/6/24	
Drawing File Name : GTQD-BLK-1939-2902				Rev	
Part Number : 1939 2902 x00				2013/6/24	

GLORYTECH TECHNOLOGY CO., LTD.