



SPECIFICATIONS:

Description	Cycles on-off when load is excessive; Blade terminals
Breaker Type	Type I
Terminals	Blades, breakable to desired length
Terminal Size	.205"(5.2mm)
Ambient Temperature Range	-40°C~+85°C
Housing Style	Narrow body case, plated steel
Mounting Method	Plug into universal blade breaker panel or into in-line connector
Usage	Battery chargers, trucks, buses,RV's, trolling motors,etc
Application	Automotive headlamp, power windows, seats & locks
Standard	Complies with SAE J553

Ordering Information:

Part Number	Ampere(A)	Voltage(VDC)
15302100000	10A	6-24V
15302150000	15A	6-24V
15302200000	20A	6-24V
15302250000	25A	6-24V
15302300000	30A	6-24V
15302400000	40A	6-24V

Electrical Characteristics:

% of Ampere Rating	Ampere Rating	Opening Time
100%	10 ~ 40 Amp	60 mins Min.
135%	10 ~ 40 Amp	60 mins Max.
200%	10 ~ 40 Amp	1 mins Max.

Vehicle Replacement Guide:

Position	Replacement Vehicle
Position A	Ford Pickup Trucks
Position B	Dodge Trucks
	Ford Pickup Trucks(Heavy) Navistar(IHC) Trucks
Position C	Kenworth Trucks

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	GLORYTECH TECHNOLOGY CO., LTD.			
	Check				
Finish	Engr	Title: Plug-In Circuit Breaker	A	GTQD-CBK-1530	B
	Appd				
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale: 1:1	Dwg Size	Sht 1 of 1	Rev
Model File Name : Plug-In Circuit Breaker					
Drawing File Name : GTQD-CBK-1530					
Part Number : 1530 xxxx 000			Date:	2004/9/24	