



Part Number	A m p e r e (A)	V o l t a g e (V)
1 3 4 1 0 0 5 0 4 4 0	5 0 m A	2 5 0 V
1 3 4 1 0 0 6 3 4 4 0	6 3 m A	2 5 0 V
1 3 4 1 0 0 8 0 4 4 0	8 0 m A	2 5 0 V
1 3 4 1 0 1 0 0 4 4 0	1 0 0 m A	2 5 0 V
1 3 4 1 0 1 2 5 4 4 0	1 2 5 m A	2 5 0 V
1 3 4 1 0 1 6 0 4 4 0	1 6 0 m A	2 5 0 V
1 3 4 1 0 2 0 0 4 4 0	2 0 0 m A	2 5 0 V
1 3 4 1 0 2 5 0 4 4 0	2 5 0 m A	2 5 0 V
1 3 4 1 0 3 1 5 4 4 0	3 1 5 m A	2 5 0 V
1 3 4 1 0 4 0 0 4 4 0	4 0 0 m A	2 5 0 V
1 3 4 1 0 5 0 0 4 4 0	5 0 0 m A	2 5 0 V
1 3 4 1 0 6 3 0 4 4 0	6 3 0 m A	2 5 0 V
1 3 4 1 0 8 0 0 4 4 0	8 0 0 m A	2 5 0 V
1 3 4 1 1 1 0 0 4 4 0	1 A	2 5 0 V
1 3 4 1 1 1 2 5 4 4 0	1 . 2 5 A	2 5 0 V
1 3 4 1 1 1 6 0 4 4 0	1 . 6 A	2 5 0 V
1 3 4 1 1 2 0 0 4 4 0	2 A	2 5 0 V
1 3 4 1 1 2 5 0 4 4 0	2 . 5 A	2 5 0 V
1 3 4 1 1 3 1 5 4 4 0	3 . 1 5 A	2 5 0 V
1 3 4 1 1 4 0 0 4 4 0	4 A	2 5 0 V
1 3 4 1 1 5 0 0 4 4 0	5 A	2 5 0 V
1 3 4 1 1 6 3 0 4 4 0	6 . 3 A	2 5 0 V
1 3 4 1 1 7 0 0 4 4 0	7 A	2 5 0 V
1 3 4 1 1 8 0 0 4 4 0	8 A	2 5 0 V
1 3 4 1 2 1 0 0 4 4 0	1 0 A	2 5 0 V
1 3 4 1 2 1 2 0 4 4 0	1 2 A	2 5 0 V
1 3 4 1 2 1 5 0 4 4 0	1 5 A	2 5 0 V
1 3 4 1 2 1 6 0 4 4 0	1 6 A	2 5 0 V
1 3 4 1 2 2 0 0 4 4 0	2 0 A	2 5 0 V
1 3 4 1 2 2 5 0 4 4 0	2 5 A	2 5 0 V

Operating Temperature : -55°C to 200°C (consider de-rating)

Interrupting Capacity : 200A/250V AC

Opening Time / Pre-arcing Time : IEC 60127-4(UMF)

In	1.25 In	2In	10In	
50mA~25A	> 1hr	Max.	Min.	Max.
		120s	10ms	100ms

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	
	Check	
Finish	Engr	
	Appd	
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		

GLORYTECH TECHNOLOGY CO., LTD.

Title: Safety Ez Fuse		A4	GTQD-FUS-1341	B
Scale:	2 : 1			

Model File Name : Ez-E7-P.C.B. , UL Slow Blow	
Drawing File Name : GTQD-FUS-1341	
Part Number : 1341 xxxx 440	Date: 2005/11/18