



Rating In OCR FONT

Specifications :

- 1.Housing Material :Nylon PA66
- 2.Terminal : Zinc alloy, tin plated
- 3.UL 248 Special Purpose Fuse



% of Rated Current	Operating Time	
	min.	max.
110%	100h	---
135%	0.75s	1800s
200%	0.15s	5s
350%	0.04s	0.5s
600%	0.02s	0.2s

According to ISO 8820-3 standard specification
Electrical Characteristics

Part No.	Rated Current	Voltage Drop	Body color
1412 1100	1A	250 mV	Black
1412 1200	2A	225mV	Grey
1412 1300	3A	200mV	Violet
1412 1400	4A	200mV	Pink
1412 1500	5A	175mV	Tan
1412 1750	7.5A	150 mV	Brown
1412 2100	10A	140 mV	Red
1412 2150	15A	125mV	Blue
1412 2200	20A	125mV	Yellow
1412 2250	25A	125mV	Natural(White)
1412 2300	30A	120mV	Green
1412 2350	35A	120mV	Blue Green
1412 2400	40A	120mV	Orange

Tolerances : Unless Otherwise Specified						
Dimension	Critical To Function	General				
< 1	+/- 0.02	+/- 0.03				
1 ~ 8	+/- 0.1	+/- 0.2				
8 ~ 24.995	+/- 0.15	+/- 0.25				
25 ~ 99.99	+/- 0.2	+/- 0.3				
Angles	+/- 1°	+/- 5°				
Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	Title:	A4	GTQD-FUS-1412	B
	Check				
Finish	Engr	Blade Type Automotive Fuse			
	Appd				
Unless Otherwise Specified Dimensions are mm (inch)					
Tolerances:					
.x = 1.0 (.04)					
.xx = 0.5 (.02)					
.xxx = 0.25 (.010)					
Model File Name : Blade Type Automotive Fuse ; 32V			Dwg Size	Sht	1 of 1
Drawing File Name : GTQD-FUS-1412			Date:	2019/7/3	
Part Number : 1412 xxxx					

GLORYTECH TECHNOLOGY CO., LTD.