



Opening Time / Pre-arcing Time:

In	1.1 In	1.35In	2.0 In	3.5 In	6.0 In
0.5 ~ 30A	Carry	Min. 0.75s Max. 1800s	Min. 0.15s Max. 30s	Min. 0.04s Max. 0.5s	Min. 0.01s Max. 0.1s
In	1.0 In	1.5In	2.0 In	3.5 In	6.0 In
35 ~ 40A	Carry	Min. 0.75s Max. 600s	Min. 0.15s Max. 30s	Min. 0.04s Max. 0.5s	Min. 0.01s Max. 0.1s

Order Information:

Part No.	Ampere(A)	Voltage(VDC)	Body color
1421 0500 200	0.5	58	D-Blue
1421 1100 200	1		Black
1421 1200 200	2		Grey
1421 1300 200	3		Violet
1421 1400 200	4		Pink
1421 1500 200	5		Tan
1421 1750 200	7.5		Brown
1421 2100 200	10		Red
1421 2150 200	15		Blue
1421 2200 200	20		Yellow
1421 2250 200	25	Natural	
1421 2300 200	30	Green	
1421 2350 200	35	Blue Green	
1421 2400 200	40	Orange	

Specifications :

Body Material : Nylon with 25% Fiberglass
 Cover Material : Nylon with 25% Fiberglass, Blue
 Metal Material : Copper Alloy, gal. Sn
 Interruption Ratings : 1000A 58VDC

GLORYTECH TECHNOLOGY CO., LTD.

Material	Drawn	
	Check	
Finish	Engr	
	Appd	

Unless Otherwise Specified
 Dimensions are mm (inch)

Tolerances:
 .x = 1.0 (.04)
 .xx = 0.5 (.02)
 .xxx = 0.25 (.010)

Model File Name : 58V Blade Fuse

Drawing File Name : GTQD-FUS-1421-58V

Part Number : 1421 xxxx 200

Title:	58V Blade Fuse			A4	GTQD-FUS-1421-58V	B
Scale:	1:1	Dwg Size	Sht	1	of	1
Rev						

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24