




Rating In OCR FONT



### Order Information:

Part No.	Ampere(A)	Body color
1422 0500 200	0.5	Dark Blue
1422 1100 200	1	Black
1422 1200 200	2	Grey
1422 1300 200	3	Violet
1422 1400 200	4	Pink
1422 1500 200	5	Tan
1422 1600 200	6	Light Red
1422 1700 200	7	Light Orange
1422 1750 200	7.5	Brown
1422 1800 200	8	Light Yellow
1422 2100 200	10	Red
1422 2120 200	12	Light Pink
1422 2150 200	15	Blue
1422 2160 200	16	Light Green
1422 2200 200	20	Yellow
1422 2250 200	25	Natural

### Electrical Characteristics:

% of Rated Current	Opening Time	
	Min.	Max.
100%	---	carry
135%	0.75s	3600s
200%	0.15s	60s
350%	0.04s	1s
600%	0.01s	0.1s

### Specifications :

Body & Cover Material : PA66 with glass fiber  
 Cover Color : Red  
 Terminal Material : Copper Alloy, Tin Plated  
 Interruption Ratings : DC80V 1000A

Tolerances : Unless Otherwise Specified			
Dimension	Critical To Function	General	
< 1	+/- 0.02	+/- 0.03	
1 ~ 8	+/- 0.1	+/- 0.2	
8 ~ 24.995	+/- 0.15	+/- 0.25	
25 ~ 99.99	+/- 0.2	+/- 0.3	
Angles	+/- 1°	+/- 5°	
Rev	EN	Description	Dwg Ckd Appd Date
B	93092401	Modify the tolerance	Kao Chyi Ku 2004/9/24

Material		Finish		Title:		Dwg Size	Sht	1 of 1	Rev
Drawn Check	Engr Appd	80V Blade Fuse	A4	GTQD-FUS-1422	B				
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)						Scale: 1:1			
Model File Name : 80V Blade Fuse Drawing File Name : GTQD-FUS-1422 Part Number : 1422 xxxx 200						Date: 2017/12/12			