



Rating In OCR FONT



Specifications :
 Body & Cover Material : PA66 with glass fiber
 Cover Color : Red
 Terminal Material : Copper Alloy, Tin Plated
 Interruption Ratings : DC80V 1000A

Electrical Characteristics:

% of Rated Current	Opening Time	
	Min.	Max.
100%	---	carry
135%	0.75s	3600s
200%	0.15s	60s
350%	0.04s	1s
600%	0.01s	0.1s

Order Information:

Part No.	Ampere(A)	Body color
1422S 0500 200	0.5	Dark Blue
1422S 1100 200	1	Black
1422S 1200 200	2	Grey
1422S 1300 200	3	Violet
1422S 1400 200	4	Pink
1422S 1500 200	5	Tan
1422S 1600 200	6	Light Red
1422S 1700 200	7	Light Orange
1422S 1750 200	7.5	Brown
1422S 1800 200	8	Light Yellow
1422S 2100 200	10	Red
1422S 2120 200	12	Light Pink
1422S 2150 200	15	Blue
1422S 2160 200	16	Light Green
1422S 2200 200	20	Yellow
1422S 2250 200	25	Natural

GLORYTECH TECHNOLOGY CO., LTD.

Title:
80V Blade Fuse-Slotted

A4 GTQD-FUS-1422S

B

Unless Otherwise Specified
 Dimensions are mm (inch)
 Tolerances:
 .x = 1.0 (.04)
 .xx = 0.5 (.02)
 .xxx = 0.25 (.010)

Material	Drawn	Scale: 1:1		Dwg Size	Sht 1 of 1	Rev
Finish	Check					
	Engr					
	Appd					

Tolerances : Unless Otherwise Specified			
Dimension	Critical To Function	General	
< 1	+/- 0.02	+/- 0.03	
1 ~ 8	+/- 0.1	+/- 0.2	
8 ~ 24.995	+/- 0.15	+/- 0.25	
25 ~ 99.99	+/- 0.2	+/- 0.3	
Angles	+/- 1°	+/- 5°	

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Model File Name : 80V Blade Fuse-Slotted	
Drawing File Name : GTQD-FUS-1422S	
Part Number : 1422S xxx 200	Date: 2019/12/6