



Order Information:

| Part No. | Ampere(A) | Voltage(VDC) | Body color |
|---------------|-----------|--------------|------------|
| 1423 0500 2IG | 0.5 | 125 | D-Blue |
| 1423 1100 2IG | 1 | | Black |
| 1423 1200 2IG | 2 | | Grey |
| 1423 1300 2IG | 3 | | Violet |
| 1423 1400 2IG | 4 | | Pink |
| 1423 1500 2IG | 5 | | Tan |
| 1423 1750 2IG | 7.5 | | Brown |
| 1423 2100 2IG | 10 | | Red |
| 1423 2150 2IG | 15 | | Blue |
| 1423 2200 2IG | 20 | | Yellow |
| 1423 2250 2IG | 25 | Natural | |
| 1423 2300 2IG | 30 | Green | |

Opening Time / Pre-arcing Time:

| In | 1.5In | | 2.0In | | 3.5In | | 6.0In | |
|-----------|-------|------|-------|------|-------|------|-------|------|
| | Min. | Max. | Min. | Max. | Min. | Max. | Min. | Max. |
| 0.5 ~ 30A | 0.75s | 600s | 0.15s | 30s | 0.04s | 0.5s | 0.01s | 0.1s |

Specifications :

Body Material : Nylon with 25% Fiberglass
 Cover Material : Nylon with 25% Fiberglass, D-Red
 Metal Material : Copper Alloy, gal. Sn
 Interruption Ratings : 1000A 125VDC
 Filled with sand

| Tolerances : Unless Otherwise Specified | | | |
|-----------------------------------------|----------------------|----------------------|-----------------------|
| Dimension | Critical To Function | General | |
| < 1 | +/- 0.02 | +/- 0.03 | |
| 1 ~ 8 | +/- 0.1 | +/- 0.2 | |
| 8 ~ 24.995 | +/- 0.15 | +/- 0.25 | |
| 25 ~ 99.99 | +/- 0.2 | +/- 0.3 | |
| Angles | +/- 1° | +/- 5° | |
| Rev | EN | Description | Dwg Ckd Appd Date |
| B | 93092401 | Modify the tolerance | Kao Chyi Ku 2004/9/24 |

| Material | Drawn | Title: | Dwg Size | Sht | 1 | of | 1 | Rev |
|------------------------------------------------------------------------------------------------------------------------------------------------|-------|------------------------|-----------|----------------------|----------|----|---|-----|
| | Check | | | | | | | |
| Finish | Appd | 125V Blade Fuse | A4 | GTQD-FUS-1423 | B | | | |
| Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010) Scale: 1:1 | | | | | | | | |
| Model File Name : 125V Blade Fuse ; Ignition Protected | | | | | | | | |
| Drawing File Name : GTQD-FUS-1423 | | | | | | | | |
| Part Number : 1423 xxxx 200 | | | | | | | | |
| Date: 2017/12/12 | | | | | | | | |

GLORYTECH TECHNOLOGY CO., LTD.