



Rating In OCR FONT



Electrical Characteristics:

% of Rated Current	Opening Time	
	Min.	Max.
100%	---	carry
150%	0.75s	3600s
200%	0.15s	60s
350%	0.04s	1s
600%	0.01s	0.1s

Order Information:

Part No.	Ampere(A)	Body color
1423 1100 2IG *	1	Black
1423 1200 2IG *	2	Grey
1423 1300 2IG *	3	Violet
1423 1400 2IG *	4	Pink
1423 1500 2IG *	5	Tan
1423 1600 2IG *	6	Light Red
1423 1700 2IG *	7	Light Orange
1423 1750 2IG *	7.5	Brown
1423 1800 2IG *	8	Light Yellow
1423 2100 2IG *	10	Red
1423 2120 2IG *	12	Light Pink
1423 2150 2IG *	15	Blue

* = G, Gold Plated
 * = S, Silver Plated

Specifications :

Body & Cover Material : Thermoplastics
 Cover Color : Dark Red
 Terminal Material : Copper Alloy, Tin Plated
 Interruption Ratings : DC 125V 1000A
 Filled with sand

Tolerances : Unless Otherwise Specified			
Dimension	Critical To Function	General	
< 1	+/- 0.02	+/- 0.03	
1 ~ 8	+/- 0.1	+/- 0.2	
8 ~ 24.995	+/- 0.15	+/- 0.25	
25 ~ 99.99	+/- 0.2	+/- 0.3	
Angles	+/- 1°	+/- 5°	
Rev	EN	Description	Dwg Ckd Appd Date
B	93092401	Modify the tolerance	Kao Chyi Ku 2004/9/24

Material		Title:	
Drawn	Check	125V Blade Fuse	
Engr	Appd	A4 GTQD-FUS-1423 B	
Finish		Unless Otherwise Specified	
Dimensions are mm (inch)		Tolerances:	
.x = 1.0 (.04)		Scale: 1:1	
.xx = 0.5 (.02)		Dwg Size	
.xxx = 0.25 (.010)		Sht 1 of 1	
Model File Name : 125V Blade Fuse ; Ignition Protected			
Drawing File Name : GTQD-FUS-1423			
Part Number : 1423 xxx 2IG		Date: 2017/12/12	

GLORYTECH TECHNOLOGY CO., LTD.