



Adapter :
For 110 female disconnecter(2.8x0.5mm)

Electrical Characteristics:

% of Rated Current	Opening Time	
	Min.	Max.
100%	carry	---
135%	0.75s	3600s
200%	0.15s	60s
350%	0.04s	1s
600%	0.01s	0.1s

Specifications :
 Body & Cover Material : Thermoplastics
 Cover Color : White
 Terminal Material : Copper Alloy, Tin Plated
 Interruption Ratings : DC80V 1000A
 Circuit 1+2 : 40A max.
 Circuit 2 : 15A max.

Order Information:

Part No.	Amperre(A)	Body color
1424 2100 200 *	10	Red
1424 2120 200 *	12	Light Pink
1424 2150 200 *	15	Blue
1424 2160 200 *	16	Light Green
1424 2200 200 *	20	Yellow
1424 2250 200 *	25	Natural
1424 2300 200 *	30	Green

* = G, Gold Plated
 * = S, Silver Plated

Tolerances : Unless Otherwise Specified			
Dimension	Critical To Function	General	
< 1	+/-0.02	+/-0.03	
1 ~ 8	+/-0.1	+/-0.2	
8 ~ 24.995	+/-0.15	+/-0.25	
25 ~ 99.99	+/-0.2	+/-0.3	
Angles	+/-1°	+/-5°	
Rev	EN	Description	Dwg Ckd Appd Date
B	93092401	Modify the tolerance	Kao Chyi Ku 2004/9/24

Material		Finish		Title:	
Drawn	Check	Engr	Appd	Fuse Tap Adapter Type	A4
				Blade Fuse	GTQD-FUS-1424
Unless Otherwise Specified Dimensions are mm (inch)				Tolerances:	
.x = 1.0 (.04)				Scale: 2:1	
.xx = 0.5 (.02)				Dwg Size	
.xxx = 0.25 (.010)				Sht 1 of 1	
Model File Name : Fuse Tap Adapter Type Blade Fuse ; 80V					
Drawing File Name : GTQD-FUS-1424					
Part Number : 1424 xxxx 200					
Date:					2021/4/20
					Rev

GLORYTECH TECHNOLOGY CO., LTD.