



Order Information:

Part No.	Ampere(A)	Body color
1431 0500 200	0.5	Dark Blue
1431 1100 200	1	Black
1431 1200 200	2	Grey
1431 1300 200	3	Violet
1431 1400 200	4	Pink
1431 1500 200	5	Tan
1431 1600 200	6	Light Red
1431 1700 200	7	Light Orange
1431 1750 200	7.5	Brown
1431 1800 200	8	Light Yellow
1431 2100 200	10	Red
1431 2120 200	12	Light Pink
1431 2150 200	15	Blue
1431 2160 200	16	Light Green
1431 2200 200	20	Yellow
1431 2250 200	25	Natural
1431 2300 200	30	Green

Opening Time / Pre-arcing Time:

% of Rated Current	Opening Time	
	0.5 ~ 16A	20 ~ 30A
100%	carry	
135%	0.75 ~ 3600s	
200%	0.15 ~ 5s	0.15 ~ 60s
350%	0.02 ~ 1s	
600%	0.01 ~ 0.1s	

Specifications :

Body Material : Nylon with 25% Fiberglass
 Cover Material : Nylon with 25% Fiberglass, Blue
 Metal Material : Copper Alloy, gal. Sn
 Interruption Ratings : 1000A 58VDC

Tolerances : Unless Otherwise Specified			
Dimension	Critical To Function	General	
< 1	+/- 0.02	+/- 0.03	
1 ~ 8	+/- 0.1	+/- 0.2	
8 ~ 24.995	+/- 0.15	+/- 0.25	
25 ~ 99.99	+/- 0.2	+/- 0.3	
Angles	+/- 1°	+/- 5°	
Rev	EN	Description	Dwg Ckd Appd Date
B	93092401	Modify the tolerance	Kao Chyi Ku 2004/9/24

Material		Title:	
Drawn	Check	58V Mini Blade Fuse	
Engr			
Appd			
Unless Otherwise Specified Dimensions are mm (inch)		A4 GTQD-FUS-1431-58V B	
Tolerances:		Scale: 2:1	
.x = 1.0 (.04)		Dwg Size	
.xx = 0.5 (.02)		Sht 1 of 1	
.xxx = 0.25 (.010)		Rev	
Model File Name : 58V Mini Blade Fuse			
Drawing File Name : GTQD-FUS-1431-58V			
Part Number : 1431 xxxx 200		Date: 2017/12/12	

GLORYTECH TECHNOLOGY CO., LTD.