



### Order Information:

Part No.	Ampere(A)	Body color
1432 0500 200	0.5	Dark Blue
1432 1100 200	1	Black
1432 1200 200	2	Grey
1432 1300 200	3	Violet
1432 1400 200	4	Pink
1432 1500 200	5	Tan
1432 1600 200	6	Light Red
1432 1700 200	7	Light Orange
1432 1750 200	7.5	Brown
1432 1800 200	8	Light Yellow
1432 2100 200	10	Red
1432 2120 200	12	Light Pink
1432 2150 200	15	Blue
1432 2160 200	16	Light Green
1432 2200 200	20	Yellow
1432 2250 200	25	Natural
1432 2300 200	30	Green

### Opening Time / Pre-arcing Time:

% of Rated Current	Opening Time	
	0.5 ~ 16A	20 ~ 30A
100%	carry	
135%	0.75 ~ 3600s	
200%	0.15 ~ 5s	0.15 ~ 60s
350%	0.02 ~ 1s	
600%	0.01 ~ 0.1s	

### Specifications :

Body Material : Nylon with 25% Fiberglass  
 Cover Material : Nylon with 25% Fiberglass, Red  
 Metal Material : Copper Alloy, gal. Sn  
 Interruption Ratings : 1000A 80VDC

Tolerances : Unless Otherwise Specified			
Dimension	Critical To Function	General	
< 1	+/- 0.02	+/- 0.03	
1 ~ 8	+/- 0.1	+/- 0.2	
8 ~ 24.995	+/- 0.15	+/- 0.25	
25 ~ 99.99	+/- 0.2	+/- 0.3	
Angles	+/- 1°	+/- 5°	
Rev	EN	Description	Dwg Ckd Appd Date
B	93092401	Modify the tolerance	Kao Chyi Ku 2004/9/24

Material		Title:		GLORYTECH TECHNOLOGY CO., LTD.	
Drawn	Check	80V Mini Blade Fuse		A4	GTQD-FUS-1432-80V
Engr					
Appd					
Unless Otherwise Specified Dimensions are mm (inch)		Scale: 2:1		Dwg Size	Sht 1 of 1
Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)					Rev
Model File Name : 80V Mini Blade Fuse					
Drawing File Name : GTQD-FUS-1432-80V					
Part Number : 1432 xxxx 200				Date:	2017/12/12