



Electrical Characteristics:

% of Rated Current	Opening Time	
	Min.	Max.
100%	---	carry
150%	0.75s	3600s
200%	0.15s	60s
350%	0.04s	1s
600%	0.01s	0.1s

Order Information:

Part No.	Ampere(A)	Body color
1433 1100 2IG *	1	Black
1433 1200 2IG *	2	Grey
1433 1300 2IG *	3	Violet
1433 1400 2IG *	4	Pink
1433 1500 2IG *	5	Tan
1433 1600 2IG *	6	Light Red
1433 1700 2IG *	7	Light Orange
1433 1750 2IG *	7.5	Brown
1433 1800 2IG *	8	Light Yellow
1433 2100 2IG *	10	Red
1433 2120 2IG *	12	Light Pink
1433 2150 2IG *	15	Blue

* = G, Gold Plated
 * = S, Silver Plated

Specifications :
 Body & Cover Material : Thermoplastics
 Cover Color : Dark Red
 Terminal Material : Copper Alloy, Tin Plated
 Interruption Ratings : DC125V 1000A
 Filled with sand

Tolerances :	Unless Otherwise Specified
Dimension	Critical To Function
< 1	+/- 0.02
1 ~ 8	+/- 0.1
8 ~ 24.995	+/- 0.15
25 ~ 99.99	+/- 0.2
Angles	+/- 1°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	Title:
	Check	
Engr	Appd	A4 GTQD-FUS-1433

Unless Otherwise Specified
 Dimensions are mm (inch)
 Tolerances:
 .x = 1.0 (.04)
 .xx = 0.5 (.02)
 .xxx = 0.25 (.010)

Model File Name : 125V Mini Blade Fuse ; Ignition Protected
 Drawing File Name : GTQD-FUS-1433
 Part Number : 1433 xxxx 2IG

Scale:	Dwg Size	Sht	1 of	1	Rev
2:1		1	1	1	

Date: 2017/12/12

GLORYTECH TECHNOLOGY CO., LTD.