



### Order Information:

Part No.	Ampere(A)	Voltage (VDC)	Body color
1441 1100 200	1	58	Black
1441 1200 200	2		Grey
1441 1300 200	3		Violet
1441 1400 200	4		Pink
1441 1500 200	5		Tan
1441 1750 200	7.5		Brown
1441 2100 200	10		Red
1441 2150 200	15		Blue
1441 2200 200	20		Yellow

### Opening Time / Pre-arcing Time:

In	1.1 In	1.35In	2.0 In	3.5 In	6.0 In
1 ~ 20A	> 100 hr	Min. 0.75s Max. 1800s	Min. 0.15s Max. 30s	Min. 0.04s Max. 0.5s	Min. 0.01s Max. 0.1s

### Specifications :

Body Material : Nylon with 25% Fiberglass  
 Cover Material : Nylon with 25% Fiberglass, Blue  
 Metal Material : Copper Alloy, gal. Sn  
 Interruption Ratings : 1000A 58VDC

Tolerances : Unless Otherwise Specified			
Dimension	Critical To Function	General	
< 1	+/- 0.02	+/- 0.03	
1 ~ 8	+/- 0.1	+/- 0.2	
8 ~ 24.995	+/- 0.15	+/- 0.25	
25 ~ 99.99	+/- 0.2	+/- 0.3	
Angles	+/- 1°	+/- 5°	
Rev	EN	Description	Dwg Ckd Appd Date
B	93092401	Modify the tolerance	Kao Chyi Ku 2004/9/24

Material		Title:		Dwg Size		Sht 1 of 1		Rev
Drawn	Check	58V Tiny 2(Micro2) Fuse		A4	GTQD-FUS-1441		B	
Engr	Appd	Unless Otherwise Specified Dimensions are mm (inch)		Scale: 2:1				
		Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Model File Name : 58V Tiny2(Micro2) Fuse		Date: 2018/6/12		
		Drawing File Name : GTQD-FUS-1441		Part Number : 1441 xxxx 200				

## GLORYTECH TECHNOLOGY CO., LTD.