



**SPECIFICATIONS:**

- Slow Blow, Low Voltage
- Material:\*Body:Plastic
- \*Metal:Zinc Alloy with Gold Plated
- Standard:According to SAE J 1888
- High Performance for Car Audio System
- Circuit Protection to Replace Fusible Wire or Fusible Link
- Fuse Are Color-Coded For Easy Amperage Identification
- Breaking Capacity : 1000A 32VDC

\*Notes : Unless Otherwise Specified

Electrical Characteristics:

% of Ampere Rating	Ampere Rating	Opening Time
135%	20 ~ 120 A	60Sec. Min. ; 3600Sec. Max.
200%	20 ~ 120 A	2Sec. Min. ; 60Sec. Max.
350%	20 ~ 120 A	0.2Sec. Min. ; 7Sec. Max.
600%	20 ~ 120 A	0.04Sec. Min. ; 1Sec. Max.

Ordering Information:

Part Number	Ampere Rating	Voltage Rating	Body Color
1501 2200 400	20A	32V	Yellow
1501 2300 400	30A	32V	Green
1501 2350 400	35A	32V	Brown
1501 2400 400	40A	32V	Orange
1501 2500 400	50A	32V	Red
1501 2600 400	60A	32V	Blue
1501 2700 400	70A	32V	Tan
1501 2800 400	80A	32V	Natural
1501 3100 400	100A	32V	Violet
1501 3120 400	120A	32V	Purple

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	<b>GLORYTECH TECHNOLOGY CO., LTD.</b>			
	Check				
Finish	Engr	<b>Title:</b> <b>Max-Blade Type Automotive Fuse</b>	<b>A</b>	<b>GTQD-FUS-1501</b>	<b>B</b>
	Appd				
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale: 1:1	Dwg Size	Sht 1 of 1	Rev
Model File Name : Max-Blade Type Automotive Fuse					
Drawing File Name : GTQD-FUS-1501					
Part Number : 1501 xxxx 400			Date:	2004/9/24	