



Specifications :

Body Material :

Rating for Polycarbonate , "@" = 0

Rating for Polycarbonate UL-94V0 , "@"=1

Metal Material : Zinc Alloy

Interruption Ratings : 1000A 32VDC

Order Information:

Part No.	Ampere(A)	Voltage(VDC)	Body color
1503 1100 2@ *	1	32	Black
1503 1200 2@ *	2	32	Grey
1503 1300 2@ *	3	32	Violet
1503 1400 2@ *	4	32	Pink
1503 1500 2@ *	5	32	Tan
1503 1750 2@ *	7.5	32	Brown
1503 2100 2@ *	10	32	Red
1503 2150 2@ *	15	32	Blue
1503 2200 2@ *	20	32	Yellow
1503 2250 2@ *	25	32	Natural
1503 2300 2@ *	30	32	Green
1503 2350 2@ *	35	32	Blue Green

Opening Time / Pre-arcing Time:

% of Ampere Rating	Opening Time
100%	100 hours Min
135%	0.75 sec. Min ; 1800 sec. Max
200%	0.15 sec. Min ; 5 sec. Max
350%	0.04 sec. Min ; 0.5 sec. Max
600%	0.02 sec. Min ; 0.1 sec. Max

Rating for mould marking , "*" = 1

Rating for white hot stamping , "*" = 2

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	GLORYTECH TECHNOLOGY CO., LTD.			
	Check				
Finish	Engr	Title:		A	B
	Appd	Mini Blade Type Automotive Fuse			
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale: 2:1		Dwg Size	Sht 1 of 1
Model File Name : Mini Blade Type Automotive Fuse					
Drawing File Name : GTQD-FUS-1503					
Part Number : 1503 xxxx 2@*				Date:	2007/4/11