



SPECIFICATIONS:

- For NISSAN Car
- Fuse are Color-Coded For Easy Amperage Identification
- Female Terminations, Locking Tab
- Common Use : 25A & 30A

Electrical Characteristics:

% of Ampere Rating	Ampere Rating	Opening Time
110%	20 ~ 100 Amp	> 4 Hr.
200%		5s ~ 100s
300%		0.5s ~ 15s
500%		3s Max.

Order Informations:

Part Number	Ampere(A)	Voltage(VDC)	Body Color
1507 2200 40*	20A	32V	Light-Blue
1507 2250 40*	25A		Brown
1507 2300 40*	30A		Green
1507 2400 40*	40A		Light Green
1507 2500 40*	50A		Red
1507 2600 40*	60A		Yellow
1507 2700 40*	70A		Light Brown
1507 2800 40*	80A		Black
1507 3100 40*	100A		Blue

Option :

- * = 0 : Normal Type
- * = 1 : Indicator Type

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24
C	98030201	New Rev	Kao	Chyi	Ku	2009/3/2

Material		GLORYTECH TECHNOLOGY CO., LTD.			
Drawn	Check	Title:			
Finish	Engr	Mini Hook Type Fuse		A4	
	Appd	Link		GTQD-FUS-1507	C
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale:	1:1	Dwg Size	Sht 1 of 1
Model File Name : Mini Hook Type Fuse Link ; Option : Indicator(LED)					
Drawing File Name : GTQD-FUS-1507					
Part Number : 1507 xxxx 40*				Date:	2009/3/2