



SPECIFICATIONS:

- For Japanese Car
- Fuse are Color-Coded For Easy Amperage Identification
- Female Terminations

Electrical Characteristics:

% of Ampere Rating	Ampere Rating	Opening Time
110%	20 ~ 120 Amp	> 4 Hr.
200%	20 ~ 120 Amp	5s ~ 100s
300%	20 ~ 120 Amp	0.5s ~ 15s
500%	20 ~ 120 Amp	3s Max.

Order Informations:

Part Number	Ampere(A)	Voltage(VDC)	Body Color
15082200400	20A	32V	White
15082300400	30A	32V	Pink
15082400400	40A	32V	Green
15082500400	50A	32V	Red
15082600400	60A	32V	Yellow
15082700400	70A	32V	Brown
15082800400	80A	32V	Black
15083100400	100A	32V	Blue
15083120400	120A	32V	Gray

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	GLORYTECH TECHNOLOGY CO., LTD.			
	Check				
Finish	Engr	Title: Fuse Link	A	GTQD-FUS-1508	B
	Appd				
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale: 1:1	Dwg Size	Sht 1 of 1	Rev
Model File Name : Female Type Fuse Link					
Drawing File Name : GTQD-FUS-1508					
Part Number : 1508 xxxx 400			Date:	2004/9/24	