



**SPECIFICATIONS:**

- For Japanese Car Use
- Fuse are Color-Coded For Easy Amperage Identification
- Straight Male Terminations

**Electrical Characteristics:**

% of Ampere Rating	Ampere Rating	Opening Time
110%	20 ~ 120 Amp	> 4 Hr.
200%	20 ~ 120 Amp	5s ~ 100s
300%	20 ~ 120 Amp	0.5s ~ 15s
500%	20 ~ 120 Amp	3s Max.

**Order Informations:**

Part Number	Ampere(A)	Voltage(VDC)	Body Color
15142200400	20A	32V	White
15142300400	30A	32V	Pink
15142400400	40A	32V	Green
15142500400	50A	32V	Red
15142600400	60A	32V	Yellow
15142700400	70A	32V	Brown
15142800400	80A	32V	Black
15143100400	100A	32V	Blue
15143120400	120A	32V	Gray

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	<b>GLORYTECH TECHNOLOGY CO., LTD.</b>			
	Check				
Finish	Engr	Title: <b>Fuse Link</b>	A	GTQD-FUS-1514	B
	Appd				
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale: 1:1	Dwg Size	Sht 1 of 1	Rev
Model File Name : Straight Male Type Fuse Link					
Drawing File Name : GTQD-FUS-1514					
Part Number : 1514 xxxx 400			Date:	2004/9/24	