



**SPECIFICATIONS:**

- For Japanese Car Use
- Fuse are Color-Coded For Easy Amperage Identification
- Straight Male Terminations, Open Type

**Electrical Characteristics:**

% of Ampere Rating	Ampere Rating	Opening Time
110%	20 ~ 120 Amp	> 4 Hr.
200%		5s ~ 100s
300%		0.5s ~ 15s
500%		3s Max.

**Order Informations:**

Part Number	Ampere(A)	Voltage(VDC)	Body Color
1515 2200 40*	20A	32V	Light-Blue
1515 2300 40*	30A		Pink
1515 2400 40*	40A		Green
1515 2500 40*	50A		Red
1515 2600 40*	60A		Yellow
1515 2700 40*	70A		Brown
1515 2800 40*	80A		Black
1515 3100 40*	100A		Blue
1515 3120 40*	120A		Gray

**Option :**

- \* = 0 : Normal Type
- \* = 1 : Indicator Type

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24
C	98030206	New Rev	Kao	Chyi	Ku	2009/3/2

Material	Drawn	<b>GLORYTECH TECHNOLOGY CO., LTD.</b>			
	Check				
Finish	Engr	<b>Title:</b> Straight Male Type Fuse Link	A4	GTQD-FUS-1515	C
	Appd				
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale: 1:1	Dwg Size	Sht 1 of 1	Rev
Model File Name : Straight Male Type Fuse Link ; Option : Indicator(LED)					
Drawing File Name : GTQD-FUS-1515					
Part Number : 1515 xxxx 40*			Date:	2009/3/2	