



**SPECIFICATIONS:**

- Normal Blow Glass Tube Fuses
- 10.3 x 38.1mm ( 13/32 x 1-1/2 Inch )
- Caps: Brass with Gold plating
- Body: Glass Tube
- Element: Zinc Alloy with Gold plating
- Ampere Rating: 10 - 80 A
- Voltage Rating: 32V
- Max Voltage Rating: 80V
- Standard : UL & CSA248-14

Notes: Unless Otherwise Specified

**Electrical Characteristics:**

% of Ampere Rating	Ampere Rating	Opening Time
100%	10 ~ 80 Amp	Carry
135%	10 ~ 80 Amp	1 Hour Max.
200%	10 ~ 30 Amp	10 Sec. Max.
300%	35 ~ 80 Amp	4 Sec. Max.

**Order Information:**

Part No.	Ampere(A)	Voltage(V)
1531 2100 200	10A	32V
1531 2120 200	12A	32V
1531 2150 200	15A	32V
1531 2200 200	20A	32V
1531 2250 200	25A	32V
1531 2300 200	30A	32V
1531 2350 200	35A	32V
1531 2400 200	40A	32V
1531 2450 200	45A	32V
1531 2500 200	50A	32V
1531 2600 200	60A	32V
1531 2700 200	70A	32V
1531 2800 200	80A	32V

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	<b>GLORYTECH TECHNOLOGY CO., LTD.</b>			
	Check				
Finish	Engr	<b>Title:</b> <b>Normal Blow Glass Fuse (5AG)</b>	<b>A4</b>	<b>GTQD-FUS-1531</b>	<b>B</b>
	Appd				
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale: 1:1	Dwg Size	Sht 1 of 1	Rev
Model File Name : Normal Blow Glass Fuse (5AG)					
Drawing File Name : GTQD-FUS-1531					
Part Number : 1531 xxxx 200			Date:	2004/9/24	