



**SPECIFICATIONS:**

- Normal Blow, Low Voltage
- Material: \*Insulating Body:Bakelite  
\*Metal:Brass/Copper
- Fuse are color-coded for easy amperage identification

**Electrical Characteristics:**

% of Ampere Rating	Ampere Rating	Opening Time
150%	5 ~ 40 Amp	1 Hour Min.
250%	5 ~ 40 Amp	60s Max.

**Order Informations:**

<b>Continental Fuse DIN-72581</b>			
Part Number	Ampere(A)	Voltage(VDC)	Body Color
15381500200	5A	32V	Yellow
15381800200	8A	32V	White
15382160200	16A	32V	Red
15382250200	25A	32V	Blue

<b>Continental Fuse FIAT 9.91806</b>			
Part Number	Ampere(A)	Voltage(VDC)	Body Color
15611500200	5A	32V	Yellow
15611800200	8A	32V	Gray
15612100200	10A	32V	White
15612160200	16A	32V	Green
15612250200	25A	32V	Brown
15612400200	40A	32V	Red

<b>Continental Fuse B.N.A-709</b>			
Part Number	Ampere(A)	Voltage(VDC)	Body Color
15621500200	5A	32V	Violet
15621800200	8A	32V	Blue
15622100200	10A	32V	Green
15622160200	16A	32V	Yellow
15622250200	25A	32V	Red

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	<b>GLORYTECH TECHNOLOGY CO., LTD.</b>			
	Check				
Finish	Engr	Title: Automotive Fuse	A	GTQD-FUS-1538 GTQD-FUS-1561 GTQD-FUS-1562	B
	Appd				
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale: 3:1	Dwg Size	Sht 1 of 1	Rev
Model File Name : Automotive Fuse					
Drawing File Name : GTQD-FUS-1538(1561;1562)					
Part Number : 1538 ; 1561 ; 1562				Date:	2004/9/24