



SPECIFICATIONS:

- Normal Blow Glass Tube Fuses with Indicator
- 10.3 x 38.1mm (13/32 x 1-1/2 Inch)
- Caps: Brass with Gold plating
- Body: Glass Tube
- Element: Zinc Alloy with Gold plating
- Ampere Rating: 10 - 80 A
- Voltage Rating: 32V
- Standard : UL & CSA 248-14

Notes: Unless Otherwise Specified

Electrical Characteristics:

% of Ampere Rating	Ampere Rating	Opening Time
100%	10 ~ 80 Amp	Carry
135%	10 ~ 80 Amp	1 Hour Max.
200%	10 ~ 30 Amp	10 Sec. Max.
300%	35 ~ 80 Amp	4 Sec. Max.

Order Information:

Part No.	Ampere(A)	Voltage(V)
1540 2100 200	10A	32V
1540 2120 200	12A	32V
1540 2150 200	15A	32V
1540 2200 200	20A	32V
1540 2250 200	25A	32V
1540 2300 200	30A	32V
1540 2350 200	35A	32V
1540 2400 200	40A	32V
1540 2450 200	45A	32V
1540 2500 200	50A	32V
1540 2600 200	60A	32V
1540 2700 200	70A	32V
1540 2800 200	80A	32V

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material		Drawn	GLORYTECH TECHNOLOGY CO., LTD.			
Finish		Check	Title:		A	B
		Engr	Normal Blow Glass Fuse with Indicator (5AG)			GTQD-FUS-1540
		Appd	Scale: 1:1		Dwg Size	Sht 1 of 1
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Model File Name : Normal Blow Glass Fuse with Indicator (5AG)		Rev		
		Drawing File Name : GTQD-FUS-1540				
		Part Number : 1540 xxxx 200		Date: 2004/9/24		