



Order Information:

Part No.	Ampere(A)	Body color
1543 0500 2250	0.5	Dark Blue
1543 1100 2250	1	Black
1543 1200 2250	2	Grey
1543 1300 2250	3	Violet
1543 1400 2250	4	Pink
1543 1500 2250	5	Tan
1543 1600 2250	6	Light Red
1543 1700 2250	7	Light Orange
1543 1750 2250	7.5	Brown
1543 1800 2250	8	Light Yellow
1543 2100 2250	10	Red
1543 2120 2250	12	Light Pink
1543 2150 2250	15	Blue
1543 2160 2250	16	Light Green
1543 2200 2250	20	Yellow
1543 2250 2250	25	Natural
1543 2300 2250	30	Green
1543 2350 2250	35	Blue Green
1543 2400 2250	40	Orange

Electrical Characteristics: UL248-1, SAE

% of Rated Current	Opening Time	
	0.5 ~ 30A	35 ~ 40A
100%	---	carry
110%	carry	---
135%	0.75 ~ 3600s	---
200%	0.15 ~ 60s	
350%	0.04 ~ 1s	
600%	0.01 ~ 0.1s	

Specifications :

Body Material : PET
Terminal Material : Copper Alloy, Tin Plated
Standard : UL248 Special Purpose Fuse
Approval File No. E498356-JFHR2/8
Interruption Ratings : AC250V 400A

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chvi	Ku	2004/9/24
C	107092601	UL認證通過改版	Kao	Chvi	Ku	2018/9/26

GLORYTECH TECHNOLOGY CO., LTD.



Unless Otherwise Specified
Dimensions are mm (inch)
Tolerances:
.x = 1.0 (.04)
.xx = 0.5 (.02)
.xxx = 0.25 (.010)

Material	Drawn	Check	Engr	Appd	Title:	Scale:	Dwg Size	Sht	1 of	1	Rev
Finish					Blade Type Fuse	2:1	A4	GTQD-FUS-1543-80V-C1	C1		

Model File Name : Blade Type Fuse ; 250VDC ; UL Recognized
Drawing File Name : GTQD-FUS-1543-250V-C1
Part Number : 1543 XXXX 2250
Date: 2018/9/27