



Order Information:

Part No.	Ampere(A)	Body color
1543 0500 258	0.5	Dark Blue
1543 1100 258	1	Black
1543 1200 258	2	Grey
1543 1300 258	3	Violet
1543 1400 258	4	Pink
1543 1500 258	5	Tan
1543 1600 258	6	Light Red
1543 1700 258	7	Light Orange
1543 1750 258	7.5	Brown
1543 1800 258	8	Light Yellow
1543 2100 258	10	Red
1543 2120 258	12	Light Pink
1543 2150 258	15	Blue
1543 2160 258	16	Light Green
1543 2200 258	20	Yellow
1543 2250 258	25	Natural
1543 2300 258	30	Green
1543 2350 258	35	Blue Green
1543 2400 258	40	Orange

Electrical Characteristics: UL248-1, SAE

% of Rated Current	Opening Time	
	0.5 ~ 30A	35 ~ 40A
100%	---	carry
110%	carry	---
135%	0.75 ~ 3600s	
200%	0.15 ~ 60s	
350%	0.04 ~ 1s	
600%	0.01 ~ 0.1s	

Specifications :

Body Material : PET
 Terminal Material : Copper Alloy, Tin Plated
 Standard : UL248 Special Purpose Fuse
 Approval File No. E498356-JFHR2/8
 Interruption Ratings : DCC58V 1000A

Tolerances :	Unless Otherwise Specified
Dimension	Critical To Function
< 1	+/- 0.02
1 ~ 8	+/- 0.1
8 ~ 24.995	+/- 0.15
25 ~ 99.99	+/- 0.2
Angles	+/- 1°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24
C	107092601	UL認證通過改版	Kao	Chyi	Ku	2018/9/26

GLORYTECH TECHNOLOGY CO., LTD.

Title:
Blade Type Fuse
GTQD-FUS-1543-58V



A4 **GTQD-FUS-1543-58V** **C**

Unless Otherwise Specified
 Dimensions are mm (inch)
 Tolerances:
 .x = 1.0 (.04)
 .xx = 0.5 (.02)
 .xxx = 0.25 (.010)

Scale: 2:1

Dwg Size Sht 1 of 1 Rev

Model File Name : Blade Type Fuse ; 58VDC ; UL Recognized

Drawing File Name : GTQD-FUS-1543-58V

Part Number : 1543 XXXX 258

Date: 2018/9/27