



**Specifications :**

Body Material : Nylon with Fiber Glass  
 Cover : Thermoplastic, UL94V-0,Blue  
 Metal Material : Copper Alloy, gal. Sn  
 Element : AgCu Alloy  
 Interruption Ratings : 1000A 58VDC  
 Comply With : ISO 8820-10:2020,UL248

**Order Information:**

Part Number	Ampere Rating	Voltage Rating	Body Color
1621 2200	20A	58V	Yellow
1621 2250	25A		White
1621 2300	30A		Green
1621 2350	35A		Dark Green
1621 2400	40A		Orange
1621 2500	50A		Red
1621 2600	60A		Blue

**Opening Time / Pre-arcing Time:**

In	1.0In		1.35In		1.6 In		2.0 In		3.5 In		6.0 In	
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
20 ~ 60A	>100h	60s	3600s	10s	200s	0.15s	60s	40ms	7s	0.04s	1s	

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Chang	Huang	Ku	2023/3/24

<b>Material</b>	Drawn	<b>GLORYTECH TECHNOLOGY CO., LTD.</b>				
	Check					
<b>Finish</b>	Engr	<b>Title:</b>				
	Appd	<b>MAX Compact Blade</b>	<b>A4</b>	<b>GTQD-FUS-1621</b>	<b>B</b>	
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		<b>Type Automotive Fuse</b>				
		<b>58V</b>				
		Scale: 1:1	Dwg Size	Sht 1 of 1	Rev	
Model File Name : MAX Compact Blade Type Automotive Fuse 58V						
Drawing File Name : GTQD-FUS-1621						
Part Number : 1621 xxxx			Date:	2023/7/24		