



**Specifications :**

Body Material : Nylon with Fiber Glass  
 Cover : Thermoplastic, UL94V-0,Blue-Green  
 Metal Material : Copper Alloy, gal. Sn  
 Element : AgCu Alloy  
 Interruption Ratings : 1000A 58VDC  
 Comply With : ISO 8820-10:2020,UL248  
 Filled with sand

**Order Information:**

Part Number	Ampere Rating	Voltage Rating	Body Color
1624 2200	20A	58V	Yellow
1624 2250	25A		White
1624 2300	30A		Green
1624 2350	35A		Dark Green
1624 2400	40A		Orange
1624 2500	50A		Red
1624 2600	60A		Blue

**Opening Time / Pre-arcing Time:**

In	1.0In	1.35In		1.6 In		2.0 In		3.5 In		6.0 In	
	Min.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
20 ~ 60A	>100h	60s	3600s	10s	200s	0.15s	60s	40ms	7s	0.04s	1s

Tolerances : Unless Otherwise Specified

Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Chang	Huang	Ku	2023/3/24

Material	Drawn	<b>GLORYTECH TECHNOLOGY CO., LTD.</b>				
	Check					
Finish	Engr	Title: <b>MAX Compact Blade Type Automotive Fuse 58V Ignition Protected</b>	A4	GTQD-FUS-1624	B	
	Appd					
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale: 1:1	Dwg Size	Sht 1 of 1	Rev	
Model File Name : MAX Compact Blade Type Automotive Fuse 58V;Ignition Protected						
Drawing File Name : GTQD-FUS-1624						
Part Number : 1624 xxxx			Date:	2023/7/24		