



### Order Information:

Part Number	Ampere Rating	Voltage Rating	Body Color
1625 2200	20A	80V	Yellow
1625 2250	25A		White
1625 2300	30A		Green
1625 2350	35A		Dark Green
1625 2400	40A		Orange
1625 2500	50A		Red
1625 2600	60A		Blue

### Specifications :

Body Material : Nylon with Fiber Glass  
 Cover : Thermoplastic, UL94V-0, Pink  
 Metal Material : Copper Alloy, gal. Sn  
 Element : AgCu Alloy  
 Interruption Ratings : 1000A 80VDC  
 Comply With : ISO 8820-10:2020, UL248  
 Filled with sand

### Opening Time / Pre-arcing Time:

In	1.0In	1.35In		1.6 In		2.0 In		3.5 In		6.0 In	
	Min.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
20 ~ 60A	>100h	60s	3600s	10s	200s	0.15s	60s	40ms	7s	0.04s	1s

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Chang	Huang	Ku	2023/3/24

Material						GLORYTECH TECHNOLOGY CO., LTD.											
Drawn		Check		Engr		Appd		Title:		A4		GTQD-FUS-1625		B			
Finish						Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)						<b>MAX Compact Blade Type Automotive Fuse 80V Ignition Protected</b>		<b>Scale:</b> 1:1		<b>Dwg Size</b> Sht 1 of 1 Rev	
<b>Model File Name : MAX Compact Blade Type Automotive Fuse 80V; Ignition Protected</b>												<b>Drawing File Name : GTQD-FUS-1625</b>					
<b>Part Number : 1625 xxxx</b>								<b>Date:</b> 2023/7/24									