



Order Information:

Part Number	Ampere Rating	Voltage Rating	Body Color
1626 2200	20A	250VAC	Yellow
1626 2250	25A		White
1626 2300	30A		Green
1626 2350	35A		Dark Green
1626 2400	40A		Orange
1626 2500	50A		Red
1626 2600	60A		Blue

Specifications :

Body Material : Nylon with Fiber Glass
 Cover : Thermoplastic, UL94V-0, Brown
 Metal Material : Copper Alloy, gal. Sn
 Element : AgCu Alloy
 Interruption Ratings : 400A 250VAC
 Comply With : ISO 8820-10:2020, UL248
 Filled with sand

Opening Time / Pre-arcing Time:

In	1.0In	1.35In	1.6 In	2.0 In	3.5 In	6.0 In					
	Min.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
20 ~ 60A	>100h	60s	3600s	10s	200s	0.15s	60s	40ms	7s	0.04s	1s

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Chang	Huang	Ku	2023/3/24

Material	Drawn	GLORYTECH TECHNOLOGY CO., LTD.				
	Check	Title:				
Finish	Engr	MAX Compact Blade		A4	GTQD-FUS-1626	B
	Appd	Type Automotive Fuse				
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		250VAC				
		Scale:	1:1	Dwg Size	Sht 1 of 1	Rev
Model File Name : MAX Compact Blade Type Automotive Fuse 250VAC						
Drawing File Name : GTQD-FUS-1626						
Part Number : 1626 xxxx				Date:	2023/7/24	