



**Opening Time / Pre-arcing Time :**

In	1.0 In	2.0 In
32mA~10A	Carry	Max. 10 s

**Order Information :**

Long Lead (L=18.8mm) : Add "1" After Part No.  
1000pes Ammo Pack  
Short Lead (L=4.3mm) : Add "0" After Part No.  
Bulk Pack

Part Number	Amper e(A)	Voltage(V)
1703 0032 24 *	32 m A	250 V
1703 0040 24 *	40 m A	250 V
1703 0050 24 *	50 m A	250 V
1703 0060 24 *	60 m A	250 V
1703 0063 24 *	63 m A	250 V
1703 0080 24 *	80 m A	250 V
1703 0100 24 *	100 m A	250 V
1703 0125 24 *	125 m A	250 V
1703 0160 24 *	160 m A	250 V
1703 0200 24 *	200 m A	250 V
1703 0250 24 *	250 m A	250 V
1703 0300 24 *	300 m A	250 V
1703 0315 24 *	315 m A	250 V
1703 0400 24 *	400 m A	250 V
1703 0500 24 *	500 m A	250 V
1703 0600 24 *	600 m A	250 V
1703 0630 24 *	630 m A	250 V
1703 0700 24 *	700 m A	250 V
1703 0800 24 *	800 m A	250 V
1703 1100 24 *	1 A	250 V
1703 1125 24 *	1.25 A	250 V
1703 1150 24 *	1.5 A	250 V
1703 1160 24 *	1.6 A	250 V
1703 1200 24 *	2 A	250 V
1703 1250 24 *	2.5 A	250 V
1703 1300 24 *	3 A	250 V
1703 1315 24 *	3.15 A	250 V
1703 1350 24 *	3.5 A	250 V
1703 1400 24 *	4 A	250 V
1703 1500 24 *	5 A	250 V
1703 1630 24 *	6.3 A	250 V
1703 1700 24 *	7 A	250 V
1703 1800 24 *	8 A	250 V
1703 2100 24 *	10 A	250 V

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	<b>GLORYTECH TECHNOLOGY CO., LTD.</b>			
	Check				
Finish	Engr	Title: Subminiature Fuse	A	GTQD-FUS-1703	B
	Appd				
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale: 2:1	Dwg Size	Sht 1 of 1	Rev
Model File Name : Ez-E5 UL Quick Acting					
Drawing File Name : GTQD-FUS-1703					
Part Number : 1703 xxx 24*			Date:	2004/11/18	