



**Order Information :**

Long Lead (L=18.8mm) : Add "1" After Part No.  
 1000pcs Ammo Pack  
 Short Lead (L=4.3mm) : Add "0" After Part No.  
 Bulk Pack

Part Number	A m p e r e (A )	V o l t a g e (V )
1711 0050 24 *	50 m A	250 V
1711 0063 24 *	63 m A	250 V
1711 0080 24 *	80 m A	250 V
1711 0100 24 *	100 m A	250 V
1711 0125 24 *	125 m A	250 V
1711 0160 24 *	160 m A	250 V
1711 0200 24 *	200 m A	250 V
1711 0250 24 *	250 m A	250 V
1711 0315 24 *	315 m A	250 V
1711 0400 24 *	400 m A	250 V
1711 0500 24 *	500 m A	250 V
1711 0630 24 *	630 m A	250 V
1711 0800 24 *	800 m A	250 V
1711 1100 24 *	1 A	250 V
1711 1125 24 *	1.25 A	250 V
1711 1160 24 *	1.6 A	250 V
1711 1200 24 *	2 A	250 V
1711 1250 24 *	2.5 A	250 V
1711 1315 24 *	3.15 A	250 V
1711 1400 24 *	4 A	250 V
1711 1500 24 *	5 A	250 V
1711 1630 24 *	6.3 A	250 V
1711 1700 24 *	7 A	250 V
1711 1800 24 *	8 A	250 V
1711 2100 24 *	10 A	250 V

**Opening Time / Pre-arcing Time :**

In	1.5 In	2.1In	2.75In	4In	10In		
50mA~10A	Carry	Max.	Min.	Max.	Min.	Max.	Max.
		30 minutes	10ms	3s	3ms	300ms	20ms

Tolerances : Unless Otherwise Specified

Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn		<b>GLORYTECH TECHNOLOGY CO., LTD.</b>				
	Check						
Finish	Engr		Title: Subminiature Fuse	A	GTQD-FUS-1711	B	
	Appd						
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)			Scale:	2:1	Dwg Size	Sht 1 of 1	Rev
Model File Name : Ez-R5 IEC Quick Acting							
Drawing File Name : GTQD-FUS-1711							
Part Number : 1711 xxxx 24*				Date:	2004/11/18		