



Part Number	A m p e r e (A)	V o l t a g e (V)
1714 0032 44*	32 m A	250 V
1714 0050 44*	50 m A	250 V
1714 0060 44*	60 m A	250 V
1714 0063 44*	63 m A	250 V
1714 0080 44*	80 m A	250 V
1714 0100 44*	100 m A	250 V
1714 0125 44*	125 m A	250 V
1714 0160 44*	160 m A	250 V
1714 0200 44*	200 m A	250 V
1714 0250 44*	250 m A	250 V
1714 0300 44*	300 m A	250 V
1714 0315 44*	315 m A	250 V
1714 0400 44*	400 m A	250 V
1714 0500 44*	500 m A	250 V
1714 0600 44*	600 m A	250 V
1714 0630 44*	630 m A	250 V
1714 0700 44*	700 m A	250 V
1714 0800 44*	800 m A	250 V
1714 1100 44*	1 A	250 V
1714 1125 44*	1.25 A	250 V
1714 1150 44*	1.5 A	250 V
1714 1160 44*	1.6 A	250 V
1714 1200 44*	2 A	250 V
1714 1250 44*	2.5 A	250 V
1714 1300 44*	3 A	250 V
1714 1315 44*	3.15 A	250 V
1714 1350 44*	3.5 A	250 V
1714 1400 44*	4 A	250 V
1714 1500 44*	5 A	250 V
1714 1630 44*	6.3 A	250 V
1714 1700 44*	7 A	250 V
1714 1800 44*	8 A	250 V
1714 2100 44*	10 A	250 V

Opening Time / Pre-arcing Time :

In	1.0 In	2.0 In
32mA~10A	Carry	Max. 60 s

Order Information :

Long Lead (L=18.8mm) : Add "1" After Part No.
1000pcs Ammo Pack
Short Lead (L=4.3mm) : Add "0" After Part No.
Bulk Pack

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	GLORYTECH TECHNOLOGY CO., LTD.			
	Check				
Finish	Engr	Title: Subminiature Fuse	A4	GTQD-FUS-1714	B
	Appd				
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale: 2:1	Dwg Size	Sht 1 of 1	Rev
Model File Name : Ez-R5 UL Time Lag					
Drawing File Name : GTQD-FUS-1714					
Part Number : 1714 xxxx 44*			Date:	2004/9/24	