



MOUNTING DETAIL

SPECIFICATIONS :

1. Suitable Rated Current : 10A Max.
2. Dielectric Strength for 60 seconds : AC 3000V Min
3. Contact Resistance at 1A DC : 5mΩ Max.
4. Insulation Resistance at 500V DC : 100MΩ Min.
5. Type : Screw Knob
6. Molded Parts : Phenolic
7. Terminals : Brass

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	GLORYTECH TECHNOLOGY CO., LTD.			
	Check				
Finish	Engr	Title: Panel Mount Fuse Holder	A	GTQD-HLD-1811-0505	B
	Appd				
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale: 1:1	Dwg Size	Sht 1 of 1	Rev
Model File Name : Panel Mount Fuse Holder for 5x20mm Fuses					
Drawing File Name : GTQD-HLD-1811-0505					
Part Number : 1811 0505 521			Date:	2004/9/24	