



MOUNTING HOLES

SPECIFICATIONS :

- Suitable Rated Current : 10A 250V AC Max.
- Dielectric Strength for 60 seconds : AC3000V Min.
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Type : Bayonet Knob
- Molded Parts : P.B.T.
- Terminals : 0.5t Brass with Tin Plated
- Approval : UL Recognized E256971

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Material	Drawn	GLORYTECH TECHNOLOGY CO., LTD.				
	Check					
Finish	Engr	Title:		A4	GTQD-HLD-1816-0504	D
	Appd	P.C.B. Fuse Holder				
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale:	2 : 1	Dwg Size	Sht 1 of 1	Rev
Model File Name : P.C.B. Fuse Holder for 5x20mm Fuses (H41)						
Drawing File Name : GTQD-HLD-1816-0504						
Part Number : 1816 0504 421				Date:	2010/9/13	

Rev	EN	Description	Dwg	Ckd	Appd	Date
C	94120607	圖面修改	Chris	Bruce	Chyi	2005/12/6
D	99091303	圖面修改	Kao	Chyi	Ku	2010/9/13