



SPECIFICATIONS:

Suitable Rated Current 250V : 1.6W/6.3A Max.

Contact Resistance at 1A DC : 5mΩ Max.

Insertion & Extraction Force : 1Kg. Min. / 0.6Kg. Max.

Molded Parts : Thermoplastic, 94V0, 3.0mm Height

Terminals : Copper Alloy, Solderable, Tinned

Approval : UL Recognized E256971

Soldering Heat Resistance : 280°C 10sec. Max.(Wave)

Tolerances : Unless Otherwise Specified						
Dimension	Critical To Function	General				
< 8	+/- 0.1	+/- 0.2				
8 ~ 24.995	+/- 0.15	+/- 0.25				
25 ~ 99.99	+/- 0.2	+/- 0.3				
Angles	+/- 1°	+/- 5°				
Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24
C	94120606	圖面修改	Chris	Bruce	Chyi	2005/12/6

Material	Drawn	GLORYTECH TECHNOLOGY CO., LTD.				
	Check	Title:				
Finish	Engr	Fuse Holder		A4	GTQD-HLD-1816-0802	C
	Appd	Unless Otherwise Specified Dimensions are mm (inch)				
Tolerances:		Scale:	2.5 : 1	Dwg Size	Sht 1 of 1	Rev
.xx = 0.5 (.02)		Model File Name : Fuse Holder for Subminiature Fuse (MH2)				
.xxx = 0.25 (.010)		Drawing File Name : GTQD-HLD-1816-0802				
Part Number : 1816 0802 400				Date:	2005/12/6	