



**SPECIFICATIONS:**

- Suitable Rated Current : 30A Max.
- Dielectric Strength for 60 Seconds : AC 1500V Min
- Insertion & Extraction Force : 1kg. Min
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Voltage Drop : 20mV Max.
- Temperature Rise : 50°C Max.
- Wire : UL 1015 , 12" Loop
- Type : Water Resistant Type
- Molded Parts : P.V.C.
- Terminals : Brass

Part No.	Wire Size
18221901410	10AWG
18221901421	12AWG
18221901414	14AWG

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	<b>GLORYTECH TECHNOLOGY CO., LTD.</b>			
	Check				
Finish	Engr	Title: <b>In-Line Fuse Holder</b>	A4	GTQD-HLD-1822-1901	B
	Appd				
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale: 1:1	Dwg Size	Sht 1 of 1	Rev
Model File Name : In-Line Fuse Holder for Blade Type Fuses					
Drawing File Name : GTQD-HLD-1822-1901					
Part Number : 1822 1901 4XX			Date:	2004/9/24	